



















Panel	Applications	Coverage	Rib	Panel Attachment	Gauges	Coatings
 <p>26" Overall 24" Coverage 1-1/4"</p> <p>1/4"</p> <p>1 1/4 Corrugated</p>	Roof and Wall	24"	1 1/4" Spacing 1/4" Height	Exposed Fastening System	29, 26	Galvalume Plus®, G-40 Galvanized
 <p>26" Overall 24" Coverage 2-1/2"</p> <p>1/2"</p> <p>2 1/2 Corrugated</p>	Roof and Wall	24"	2 1/2" Spacing 1/2" Height	Exposed Fastening System	29, 26	Galvanized, Galvalume Plus®, Signature® 200
 <p>24" Overall 12" Spacing 1/2"</p> <p>5V Crimp</p>	Roof	24"	12" Spacing 1/2" Height	Exposed Fastening System	29, 26	Galvalume Plus®, Signature® 200, G-40 Galvanized
 <p>36" Overall 12" Spacing 7/8"</p> <p>7/8 Wide Rib®</p>	Roof and Wall	36"	12" Spacing 7/8" Height	Exposed Fastening System	29, 26	Galvanized, Galvalume Plus®, Signature® 200
 <p>36" Overall 6" Spacing 1/2"</p> <p>Ameri-Drain®</p>	Roof and Wall	36"	6" Spacing 1/2" Height	Exposed Fastening System	29, 26	Galvanized, Galvalume Plus®, Signature® 200
 <p>36" Overall 9" Spacing 3/4"</p> <p>Imperial Rib®</p>	Roof and Wall	36"	9" Spacing 3/4" Height	Exposed Fastening System	29, 26	Galvanized, Galvalume Plus®, Signature® 200
 <p>18", 16", or 12" Spacing 1 3/4" Height</p> <p>LokSeam</p>	Roof	12", 16", 18"	1 3/4" Height	Concealed Fastening System	24 (Standard), 22, 26 (Optional - 12" only)	Galvalume Plus®, Signature® 200, Signature® 300, Signature® 300 Metallic
 <p>36" Overall 9" Spacing 5/8"</p> <p>Monarch Rib®</p>	Roof and Wall	36"	9" Spacing 5/8" Height	Exposed Fastening System	29, 26	Galvanized, Galvalume Plus®, Signature® 200
 <p>32" Overall 2.67" Spacing 7/8"</p> <p>PBC</p>	Roof and Wall	32"	2.67" Spacing 7/8" Height	Exposed Fastening System	26 (Standard); 24, 22 (Optional)	Galvalume Plus®, Signature® 200, Signature® 300

Panel	Applications	Coverage	Rib	Panel Attachment	Gauges	Finishes	Coatings	UL
 <p>PBR</p>	Roof and Wall	36"	12" Spacing 1 1/4" Height	Exposed Fastening System	26 (Standard); 29, 24, 22 (Optional)	Bare, Siliconized Polyester and Kynar	Galvalume Plus®, Signature® 200, Signature® 300	UL 580 ratings, UL 263 Class A (non-combustible substrate), Class C (combustible substrate), UL 2218 Class 4 impact rating
 <p>PBU</p>	Roof and Wall	36"	6" Spacing 3/4" Height	Exposed Fastening System	26 (Standard); 29, 24, 22 (Optional)	Bare, Siliconized Polyester and Kynar	Galvalume Plus®, Signature® 200, Signature® 300	UL 2218 Impact Rating Class 4
 <p>Perma-Clad®</p>	Roof and Wall	36"	9" Spacing 5/8" Height	Exposed Fastening System	29, 26	Bare and Siliconized Polyester	Galvanized, Galvalume Plus®, Signature® 200	UL 580 rating, UL 263 (internal fire), UL 2218 Class 4 impact rating, UL 790 Class A Fire Rating
 <p>Regal Rib®</p>	Roof and Wall	36"	12" Spacing 5/8" Height	Exposed Fastening System	29, 26	Bare and Siliconized Polyester	Galvanized, Galvalume Plus®, Signature® 200	N/A
 <p>Retro-R®</p>	Roof and Wall	36"	12" Spacing 1 1/16" Height	Exposed Fastening System	29 (Standard), 26 (Optional)	Bare and Siliconized Polyester	Galvanized, Galvalume Plus®, Signature® 200	N/A
 <p>Rugged Rib®</p>	Roof and Wall	36"	9" Spacing 9/16" Height	Exposed Fastening System	29, 26	Bare and Siliconized Polyester	Galvanized, Galvalume Plus®, Signature® 200	UL 580 rating, UL 263 (internal fire), UL 2218 Class 4 impact rating, UL 790 - Class A Fire Rating
 <p>SL-16®</p>	Roof	16"	1" Height	Concealed Fastening System	29, 26	Bare and Siliconized Polyester	Galvalume Plus®, Signature® 200	UL 580 ratings, UL 790, Class A (external fire), roof assembly for UL 263 (internal fire), UL 2218 Class 4 impact rating, SL-16® carries Florida approval.